

DIGITAL PH METERS

10/11



TECHNICAL SPECIFICATIONS

PARAMETER

- ✓ RANGE 0 to 14.00 pH
- ✓ RESOLUTION 0.01 pH
- ✓ ACCURACY ± 0.01 pH
- ✓ DISPLAY $3\frac{1}{2}$ Digit LED
- ✓ TEMP. COMPENSATION Manual : 0 to 100 °C (ATC in Model LT - 10)
- ✓ INPUT IMPEDANCE $> 10^{12}$ ohms
- ✓ SLOPE CONTROL 80 to 120%
- ✓ RECORDER OUTPUT 0 to 10 mV/pH Adjustable
0 to 10 mV/100 mV Adjustable
- ✓ POWER 230 V \pm 10% AC, 50Hz
- ✓ DIMENSIONS 275 x 175 x 76 mm (L x B x H)
- ✓ SENSOR Combined pH Electrode

pH

- 0 to 14.00 pH
- 0.01 pH
- ± 0.01 pH
- $3\frac{1}{2}$ Digit LED
- Manual : 0 to 100 °C (ATC in Model LT - 10)
- $> 10^{12}$ ohms
- 80 to 120%
- 0 to 10 mV/pH Adjustable
0 to 10 mV/100 mV Adjustable
- 230 V \pm 10% AC, 50Hz
- 275 x 175 x 76 mm (L x B x H)
- Combined pH Electrode

mV

- 0 to ± 1999 mV
- 1 mV
- ± 1 mV

ACCESSORIES

- ✓ Combination pH Electrode
- ✓ Buffer Tablets 4 pH & 7 pH
- ✓ Operation Manual
- ✓ Buffer Bottles (4 pH & 7 pH)
- ✓ Dust Cover
- ✓ Temperature Probe (in Model LT - 10)
- ✓ Electrode Stand

